

TECHNICAL DATA SHEET

CH8930 Code 6600

Aircraft Paint Stripper (Neutral Phenolic)

DESCRIPTION

Callington CH8930 is a thickened non-flammable, neutral phenolic paint stripper for the removal of epoxy, polyurethane and other chemically resistant coatings, including primers and base coats on aircraft surfaces.

FEATURES & BENEFITS

- Non-flammable neutral phenolic paint stripper
- Removes epoxy and 2 pack coatings, including primer and base coats
- Heavy bodied, viscous material clings to vertical and inverted surfaces
- Amber colour, and low odour
- Non-corrosive to aluminium, cadmium, high strength steel and all aircraft metal surfaces

CH8930 Aircraft Paint Stripper (Neutral Phenolic) Non-flammable and non-corrobre Slow expecution rate and extended working life Compiler with Robota (B50/32, AMS 1375, Despite of B. Nill-Re1995A Collington Share— 20L

APPLICATION

Precaution: CH8930 is damaging to acrylics, most plastics, and composites. Avoid contact to prevent damage.

- 1. Clean any soiled or oily surfaces prior to stripping.
- 2. Mask off all Perspex, plastic, and rubber components.
- To avoid unnecessary evaporation, carry out stripping operation away from direct sunlight or wind.
- 4. Apply CH8930 by spray or brush. For spraying, use a Graco barrel pump or equivalent.
- 5. Once paint film has blistered, agitate area with stiff bristle brush if necessary and then rinse off with high pressure water or scrape and rinse off.

APPROVALS

Callington CH8930 has been tested and qualified to the following specifications.

- Boeing BSS7432
- AMS 1375B
- Douglas CSD1, Type III
- MIL-PRF-25134C
- MIL-R-81294B



TECHNICAL DATA SHEET

SAFETY PRECAUTIONS

CH8930 contains strong solvents and phenol, therefore care must be taken and contact with skin and eyes should be avoided. Avoid breathing vapour or spray mist. The operator is advised to wear protective clothing, gloves and eye protection.

ORDERING INFORMATION

Product Code	Packaging	Units/Carton
6600/51	20 litres	Each
6600/64	200 litres	Each

PHYSICAL PROPERTIES

Density: 1.19 ± 0.01 g/mL
Colour: Light Amber to Brown
Transparency: Translucent to Opaque

Viscosity at 20°C: 75 ± 15 Ps (Spindle #5, 20 rpm)

DANGER

Toxic if swallowed. Toxic in contact with skin. Toxic if inhaled. Causes severe skin burns and eye damage. Suspected of causing genetic defects. Suspected of causing cancer. May cause damage to organs. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life.

PRECAUTION

Obtain special instructions before use. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid release to the environment.

FIRST AID

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

STORAGE & DISPOSAL

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local regulations.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 13 September 2019 Date Printed 29/11/2023 1:50 PM