

TECHNICAL DATA SHEET

SYN 30

Code 7120

General Purpose Synthetic Metalworking Coolant

DESCRIPTION

Callington SYN 30 is a mineral-oil free, oil rejecting, synthetic metalworking coolant. It is designed for various grinding for light to medium duty machining applications on cast iron and ferrous alloys.

It is for use in soft and hard water and exhibits low foam with excellent stability under a wide range of conditions, providing outstanding machine cleanliness for longer life.

FEATURES & BENEFITS

- Rejection of tramp oil for easy removal, providing excellent machine and component cleanliness.
- Low foaming in all water conditions, ensuring continuous machining, and eliminating use of antifoams.
- Excellent stability and resistance to microbial growth, providing extremely long fluid life, and reducing fluid and waste treatment costs.
- Mineral oil, chlorine, phenol and nitrite free, environmentally friendly.
- Excellent corrosion protection even in hard water conditions.



APPLICATION

Callington SYN 30 is designed for use in most grinding operations including surface, cylindrical and centre less grinding. It is also used in honing, as well as general machining applications, such as boring, turning, milling and light duty drilling operations. It is suitable for use on cast iron, low carbon and free cutting steels, alloy steels and stainless steel.

Callington SYN 30 is extremely stable over a wide range of water conditions (0-400ppm hardness), provides excellent corrosion protection and is very clean in use, reducing product usage and maintenance requirements. It is equally suitable for use in large centralised coolant systems and for small individual coolant sumps.

TECHNICAL DATA SHEET

RECOMMENDED DILUTIONS

Material	Cast Iron	Low Carbon/ High Carbon Steels	Alloy Steels
Operation			
Grinding	4%	4%	6%
Honing			
Turning			
Boring	5%	5%	6%
Milling			
Drilling	5%	6%	8%

TYPICAL DATA (note: data is typical and does not constitute a specification)

Concentrate	Test Method	Typical Result
Appearance	Visual	Clear, Pale Yellow
Density	DIN 51757/ASTM D1298	1.067
Solution		
Appearance	Visual	Transparent
pH5%	DIN 51361/ASTM E70-97	8.7
Refractometer Factor		2.12

ORDERING INFORMATION

Product Code	Packaging
7120/51	20 litres
7120/64/AU	200 litres

STORAGE

Keep container closed, prevent exposure to frost, and prevent water ingress. Store in cool, dry conditions, avoid direct sunlight. Indoor storage is preferable.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.
Created 18 September Date Printed 13/11/2020 1:36 PM