

## TECHNICAL DATA SHEET

# ROX<sup>®</sup>CARE 230 FLEETWASH

**Code 2500***Concentrated Detergent for the Transport Industry*

### APPLICATION

Callington Haven ROX<sup>®</sup>CARE 230 is a brightly coloured concentrated all purpose degreaser and cleaner. It is designed as a heavy-duty liquid cleaner for professional pressure cleaning of road vehicles, railway, mining and large earth moving equipment.

Its well built alkaline base has enabled it to be used to clean all forms of transport equipment. It has also proved excellent for degreasing concrete floors and engines.

### BENEFITS

Callington Haven ROX<sup>®</sup>CARE 230 offers these benefits -

- Clearly identifiable colour
- Concentrated product
- Non-hazardous to the environment
- Economical
- Non-flammable

### USE DIRECTIONS

**FOR EXTERNAL CLEANING OF TRANSPORT VEHICLES:** CAUTION: Do not allow surface to dry white. Do not use stronger than 1:20 dosage on painted surfaces as this could cause paint to fade.

**HAND OPERATED PRESSURE WASHING OF TRUCKS ETC:** Allow the surface to cool before applying. Do not put detergents onto duco which is still hot. The recommended dose rate is 100ml to 500ml of ROX<sup>®</sup>CARE 230 in 20 litres of water. The rate will depend on the level of soil on the vehicle surface

Lightly spray this solution onto the surface to be cleaned at the desired level. Let this solution sit on the surface for 5 to 10 minutes. (Do not allow the solution to dry on the surface). The occasional use of a wet soft nylon broom on the surface will assist stubborn soil removal. Pressure rinse the surface clean. Working from the top of the truck down. Concentrate on wheel areas.

**HIGH PRESSURE WASHERS (TUNNEL & GANTRY TYPE):** The recommended dilution rate for these systems is 1% by volume. That is close to 200ml of ROX<sup>®</sup>CARE 230 to 20 litres of water.

**STEAM CLEANING EQUIPMENT:** Add 1 to 2 litres of ROX<sup>®</sup>CARE 230 to the detergent tank connected to the unit. Top this up with 20 litres of water then proceed as per your usual method.

... /2

## TECHNICAL DATA SHEET

ROX<sup>®</sup>CARE 230 (2500) - Page 2 of 2

### THE REMOVAL OF ALL OILS AND DEGREASING OF CONCRETE FLOORS, ENGINES AND CHASSIS BY:

**MANUAL CLEANING:** Use the product neat or diluted with up to 8 parts water. Sprinkle or spray the solution onto the surface to be cleaned. Use a hard nylon bristle broom to work the concentrate into the surface. Leave 5 minutes and pressure rinse.

### SAFETY PRECAUTIONS

ROX<sup>®</sup>CARE 230 is alkaline, it contains alkali salts. Avoid contact with skin and eyes. The wearing of gloves is recommended when handling or using this product.

### FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre.

If swallowed, **do not** induce vomiting. Give a glass of water.

For splashes to the skin, remove contaminated clothing and wash skin thoroughly. For splashes to the eye, hold eyes open and flush with copious amounts of water for 15 minutes and call a doctor.

Refer to the Material Safety Data Sheet for further information.

### PACKAGING

Available in 5 litre, 20 litre and 200 litre containers.

**WARRANTY** – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 8 January 2009 Date Printed 28/03/2018 9:25 PM